ALLROUNDER

- ✓ With fluid recovery system
- ✓ Integrate high quality swivel
- ✓ Ready to use



Mosmatic Allrounder with recovery is ideal for smaller and hard to reach areas both indoors and out. Small compact and lightweight design is ideal for jobs large or small. Using your vac system, water can be recovered, reused or discharged.



TECHNICAL DATA

Pressure Temperature Inlet







FEATURES

Recovery System

Environmental protection is more important than ever. These recovery units have a double wall housing to optimize vacuum power.

Residual water and debris can be recovered, recycled and reused.



Rotor Arms

Can withstand up to 275 bar, are precision welded and balanced.

2w2 (2 Arms / 2 Nozzles) 2w2 (2 Arms / 2 Nozzles) Part No. 82.621 (ø150mm) Part No. 82.623 (ø250mm)





Developed by Mosmatic and in service for years, the toggle swivel has proven itself. The toggle joint feature allows effortless cleaning of walls and angled surfaces. The movement of the joint is adjustable for fatigue free cleaning.

KDYF Toggle Swivel

Part No. 58.908

Swiss Engineering

High rpm stainless steel swivel, features reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.

DYF Swivel

Part No. 58.000 (ø200mm) Part No. 58.250 (ø410mm)

Stainless Steel Caster

Heavy duty ø60mm casters with custom mounting brackets ensure easy manoeuvring even in confined spaces.

Stainless Steel Caster Part No. 80.943

Caster for ø200mm Part No. 80.922



							HP-	
Name	Part No.	ø	Weight	Swivel	Rotor Arm	Nozzles	Gun	Wheels
FL-AEB 200	78.230	200	2.8kg	1x DYF	2x 1/8" NPTF	2x 1503	1x	
FL-AER 200	78.240	200	4.2kg	1x KDYF	2x 1/8" NPTF	2x 1503	1x	3x ø42
FL-AER 300	78.242	300	5.6kg	1x KDYF	2x 1/8" NPTF	2x 1503	1x	3x ø60
FL-AER 410	78.249	410	9.0kg	1x DYF	2x 1/8" NPTF	2x 1503	1x	3x ø60





